



STANDARD FEATURES



Control panel	ELECTRONIC DIGIT2
Wash arm	1 - Stainless steel
Rinse arm	2 - PP
Detergent injector	Optional
Rinse aid injector	Standard
Peristaltic rinse aid injector	Optional
Break tank	-
Water softener	Optional
Drain pump	Optional
Diagnose Wi-Fi	-

TECHNICAL FEATURES

External size	423x466x589	LxPxH	[mm]
Overall size	710	DOA	[mm]
Clearance	220	A	[mm]
Maximum height for crockery	205	Au	[mm]
Rack size	350x350		[mm]
Tank size	11		[lt]
Rinse water consumption	2,4		[lt]
Wash pump	0,17		[kW]
Tank heater element	1,6		[kW]
Booster heater element	2,6		[kW]
Installed load	2,8		[kW]
Cycles	60 / 120 / 180 / 480		[sec]
Output cycles per hour	60 / 30 / 20 / 8		[cycle/h]
Electrical supply	230V/50Hz		
Noise	48		[dBA]
Weight	26		[kg]

Theoretical data with water supply at 55°C

Where water hardness exceeds 8,43°e, a water softener is required. Not suitable for hot water over 30°C

Dimension depending on the type of basket used.



GLASSWASHER

DS G35-20



STANDARD EQUIPMENT

Hoses (1 for each): Water connection, drain, transparent for rinse product
2 universal baskets, 1 cutlery rack

GENERAL FEATURES

- Double-skinned cabinet and door.
- Tank and door made of stainless steel AISI 304.
- Easy-clean-dual-filter system.
- Pressed basket guides in the tank.
- Monobloc wash pump fixed directly to the tank.
- A stainless-steel wash arm and two rinse arms of composite material, independent and rotary.
- Integral rinse aid dosing unit.
- Digital control panel (DIGIT2).
- Four purpose-designed washing cycles for various types of crockery to be washed.

PERFORMANCES

	55°C nom.	15	20	25	30	35	40	45	50	55	60	[°C]
Supply water temperature												
Maximum cycles feasible in continuous operation	48	24	25	28	30	33	37	42	48	48	48	[rack/h]
Total spending power from single-skin machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Total spending power from double-skin machine	2,80	2,75	2,75	2,74	2,74	2,74	2,81	2,81	2,80	2,80	2,80	[kW]
Sensible heat emitted into the room from single-skinned machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Sensible heat emitted into the room from double-skinned machine	0,30	0,33	0,33	0,33	0,33	0,32	0,32	0,31	0,30	0,30	0,30	[kW]
Latent heat emitted into the room	0,45	0,08	0,10	0,12	0,16	0,20	0,25	0,32	0,40	0,45	0,50	[kW]
Emitted standby power with closed door in single-skin machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Emitted standby power with closed door in double-skin machine	0,10	0,10	0,10	0,10	0,10	0,10	0,10	0,10	0,10	0,10	0,10	[kW]