



STANDARD FEATURES



Control panel	ELECTROMECHANICAL
Wash arm	1 - Stainless steel
Rinse arm	2 - PP
Detergent injector	Optional
Rinse aid injector	Standard
Peristaltic rinse aid injector	Optional
Break tank	-
Water softener	Optional
Drain pump	Optional
Diagnose Wi-Fi	-

TECHNICAL FEATURES

External size	465x510x695	LxPxH	[mm]
Overall size	855	DOA	[mm]
Clearance	320	A	[mm]
Maximum height for crockery	305	Au	[mm]
Rack size	400x400		[mm]
Tank size	12		[lt]
Rinse water consumption	2,4		[lt]
Wash pump	0,17		[kW]
Tank heater element	1,6		[kW]
Booster heater element	2,8		[kW]
Installed load	3,0		[kW]
Cycles	120		[sec]
Output cycles per hour	30		[cycle/h]
Electrical supply	230V/50Hz		
Noise	48		[dBA]
Weight	31		[kg]

Theoretical data with water supply at 55°C

Where water hardness exceeds 8,43°e, a water softener is required. Not suitable for hot water over 30°C

Dimension depending on the type of basket used.



STANDARD EQUIPMENT

Hoses (1 for each): Water connection, drain, transparent for rinse product
1 universal basket, 1 cutlery rack

GENERAL FEATURES

- Single-skinned cabinet with double-skinned door.
- Tank and door made of stainless steel AISI 304.
- Monobloc wash pump fixed directly to the tank.
- Easy-clean-dual-filter system.
- Stainless-steel wash arm and two rinse arms of composite material, all independent and rotary.
- Integral rinse aid dosing unit.
- Electromechanical control panel.

PERFORMANCES

Supply water temperature	55°C nom.	15	20	25	30	35	40	45	50	55	60	[°C]
Maximum cycles feasible in continuous operation	27	20	21	23	26	27	27	27	27	27	27	[rack/h]
Total spending power from single-skin machine	2,95	2,95	2,95	2,95	2,95	2,95	2,95	2,95	2,95	2,95	3,02	[kW]
Total spending power from double-skin machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Sensible heat emitted into the room from single-skinned machine	0,67	0,69	0,68	0,68	0,67	0,67	0,67	0,67	0,67	0,67	0,67	[kW]
Sensible heat emitted into the room from double-skinned machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Latent heat emitted into the room	0,37	0,18	0,20	0,24	0,27	0,30	0,32	0,34	0,35	0,37	0,39	[kW]
Emitted standby power with closed door in single-skin machine	0,33	0,33	0,33	0,33	0,33	0,33	0,33	0,33	0,33	0,33	0,33	[kW]
Emitted standby power with closed door in double-skin machine	-	-	-	-	-	-	-	-	-	-	-	[kW]