



STANDARD FEATURES



Control panel	ELECTROMECHANICAL
Washing arm	2 - Stainless steel
Rinse arm	2 - PP
Detergent injector	Optional
Rinse aid injector	Standard
Peristaltic rinse aid injector	Optional
Break tank	-
Softener	Optional
Drain pump	Optional
Wi-Fi	-

TECHNICAL FEATURES

FALSO	655x745x1480	[mm]
Overall size (DOA)	1.930	[mm]
Clearance (A)	430	[mm]
Maximum height for crockery (Au)	405	[mm]
Rack size	500x500	[mm]
Tank volume	30	[lt]
Boiler volume	7,0	[lt]
Rinse water consumption	2,6	[lt]
Wash pump	1,10	[kW]
Tank heater element	3,00	[kW]
Booster heater element	6,00	[kW]
Total load	7,10	[kW]
Cycles	75 / 120 / 180	[sec]
Output cycles per hour	48 / 30 / 20	[cyc/h]
Electrical supply	400V/3N/50Hz	
Rated current	10,94	[A]
Noise	68	[dBa]
Weight	108	[kg]

Theoretical data with water supply at 55°C
Where water hardness exceeds 8,43°e, a water softener is required. Not suitable for hot water over 30°C



STANDARD EQUIPMENT

1 inlet hose
 1 drain hose
 1 transparent rinse aid hose
 1 universal rack
 1 dish rack (18 s.)
 2 cutlery racks

GENERAL FEATURES

- Single-skinned cabinet.
- Tank and hood made of stainless-steel AISI 304.
- Easy-clean dual-filter system.
- Tilted wash pump.
- Two stainless-steel wash arms and two rinse arms of composite material, independent and rotary.
- Integral hydraulic rinse aid injector.
- Auto-start hood.
- Electromechanical control panel, displaying wash and rinse temperatures.

PERFORMANCES

	55°C nom.	15	20	25	30	35	40	45	50	55	60	[°C]
Supply water temperature												
Maximum cycle/hour feasible in continuous operation	44	32	34	36	39	44	44	44	44	44	44	[cyc/h]
Total spending power from single-skinned machine	5,39	6,56	6,53	6,49	6,44	6,46	6,19	5,93	5,66	5,39	5,13	[kW]
Total spending power from double-skinned machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Sensitive heat emitted into the room by a single-skinned machine	1,97	2,08	2,06	2,04	2,01	1,97	1,97	1,97	1,97	1,97	1,97	[kW]
Sensitive heat emitted into the room by a double-skinned machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Latent heat emitted into the room	2,48	1,26	1,41	1,58	1,78	2,09	2,19	2,28	2,38	2,48	2,58	[kW]
Emitted standby power with closed door by a single-skinned machine	0,83	0,83	0,83	0,83	0,83	0,83	0,83	0,83	0,83	0,83	0,83	[kW]
Emitted standby power with closed door by a double-skinned machine	-	-	-	-	-	-	-	-	-	-	-	[kW]